



C Type

### Single phase capacitors: 250 V, 50 Hz, Cylindrical

Type	Rated Voltage	Rated Capacitance	Rated Current	Dimension	QTY	Terminal type
	(V)	(KVAR)	(A)	D*H (mm)		
BKMJ0.25-3-1	250	3	12.0	Φ65*240-M12*16	13	C
BKMJ0.25-4-1	250	4	16.0	Φ65*240-M12*16	13	C
BKMJ0.25-5-1	250	5	20.0	Φ65*240-M12*16	13	C
BKMJ0.25-7.5-1	250	7.5	30.0	Φ76*240-M12*16	9	C
BKMJ0.25-8-1	250	8	32.0	Φ76*240-M12*16	9	C
BKMJ0.25-10-1	250	10	40.0	Φ86*240-M12*16	9	C
BKMJ0.25-15-1	250	15	60.0	Φ96*240-M16*25	6	C
BKMJ0.25-16-1	250	16	64.0	Φ96*240-M16*25	6	C
BKMJ0.25-18-1	250	18	72.0	Φ106*240-M16*25	6	C
BKMJ0.25-20-1	250	20	80.0	Φ106*240-M16*25	6	C
BKMJ0.25-25-1	250	25	100.0	Φ116*280-M16*25	6	C

**Technical data:**

**Temperature category:** -25°C-50°C

**Discharge resistors:** 75 V/ 3 min

**Dielectric:** MKP - metallized PP film

**Design:** dry type, non PCB

**Tandard:** IEC 60831



Website: <http://www.wascapacitor.com> Tell: 86-757-26937167 E-mail: [sales@wasvar.com](mailto:sales@wasvar.com)