



Single phase capacitors: 525 V, 50 Hz, Cylindrical

Type	Rated Voltage	Rated Capacitance	Rated Current	Dimension	QTY	Terminal type
	(V)	(KVAR)	(A)	D*H (mm)		
BKMJ0.525-5-1	525	5	9.5	Φ65*240-M12*16	13	C
BKMJ0.525-7.5-1	525	7.5	14.3	Φ65*240-M12*16	13	C
BKMJ0.525-8-1	525	8	15.2	Φ65*240-M12*16	13	C
BKMJ0.525-10-1	525	10	19.0	Φ76*240-M12*16	9	C
BKMJ0.525-12-1	525	12	22.9	Φ76*240-M12*16	9	C
BKMJ0.525-15-1	525	15	28.6	Φ86*240-M12*16	9	C
BKMJ0.525-16-1	525	16	30.5	Φ86*240-M12*16	9	C
BKMJ0.525-18-1	525	18	34.3	Φ96*240-M16*25	9	C
BKMJ0.525-20-1	525	20	38.1	Φ96*240-M16*25	6	C
BKMJ0.525-22-1	525	22	41.9	Φ96*240-M16*25	6	C
BKMJ0.525-25-1	525	25	47.6	Φ106*240-M16*25	6	C
BKMJ0.525-30-1	525	30	57.1	Φ116*240-M16*25	6	C

Technical data:

Temperature category: -25°C-50°C

Discharge resistors: 75 V/ 3 min

Dielectric: MKP - metallized PP film

Design: dry type, non PCB

Tandard: IEC 60831



Website: <http://www.wascapacitor.com> Tell: 86-757-26937167 E-mail: sales@wasvar.com